



KNOCKOUT TANKS

SIZES AND DESIGN TO SUIT YOUR REQUIREMENTS



NEED A KNOCKOUT? GIVE US A CALL!

FAV Systems Inc. manufactures a wide range of fluid knockout tanks in different sizes and configurations. FAV Systems can either build from existing drawings, or custom design units best suited to your applications. Optional heating, insulation, coatings and colours are available.




Double Walled
Below or Above Ground
Std. sizes: 25, 50, 100 bbl

Features:

- Inlet/outlet sizes vary by capacity
- 6" still well for level indication
- 3" pump out stinger
- 3" spare
- 2" secondary containment monitor stinger & vacuum relief
- 10 ft. Connection extension (underground only)
- Varying nozzle sizes



Secondary Containment
Above Ground
Std. sizes: 4, 25, 50, 100 bbl

Features (4 bbl):

- 3" Inlet/outlet
- 3" spare
- 2" NPT spare
- 2" NPT pump out

Features (25 - 100 bbl):

- Inlet/outlet sizes vary by capacity
- 6" float bridle with sight glass - c/w 2" connections
- Level switch connections
- 3" spare
- 2" drain

ALL SIZES AVAILABLE
STORAGE CAPACITIES 4 BBL UP TO 100 BBL



Sheltered Secondary Containment
Above Ground
Std. sizes: 4, 25, 50, 100 bbl

FEATURES:

- Same as secondary containment
- Adds 2" thermal panel galvalume building

MODEL	INSTALLATION	CONTAINMENT	STANDARD SIZES (bbl)	INSULATION	HEATING/INTERNAL COATING
Double Walled	Below or above ground	Double-Walled	25, 50, 100	Optional	Optional
SKO - Contained	Above Ground	Secondary	4, 25, 50, 100	Optional	Optional
SKO - Sheltered	Above Ground	Secondary	25, 50, 100	Yes	Optional

SPECIALIZED IN PREVENTING FUGITIVE EMISSIONS

Contact: 1 (956) 589 8832

www.favsystems.com